

CEMTEC CRACK FILLER

CRACK FILLER / FAIR COAT WALL PLASTER

CEMTEC CRACK FILLER is high performance polymer modified crack filler/ fair coat wall plaster. This product can be used for filling cracks upto a width of 8mm in the concrete surfaces.

PRIMARY APPLICATIONS:

- Filling cracks, holes in the concrete
- Levelling uneven surfaces
- For smoothening cracks and holds at door frames.
- Can be used for interior / exterior applications.

FEATURES/BENEFITS:

- Normal setting times increase workability and reduce waste.
- Fill all cracks and levels the plastered surface and when sanded gives a smooth finish.
- Polymer modified ensures good bonding /flexural strength.
- Can be used in dry as well as wet areas.

SPECIFICATIONS/COMPLIANCES:

CEMTEC CRACK FILLER complies with the requirements of ASTM C 473-97 Clause 10 and ASTM C 587-97 Clause-5.

TECHNICAL INFORMATION:

Working Life	: Approx 1 hour
Fresh wet density	: Approx 1700 kg/m ³
Water addition	: 0.48 liter / kg
Color	: White powder

Note : Working life and setting time will vary dependent on ambient and substrate temperature.

SHELF LIFE:

12 months when stored at shaded dry place in original un-opened bags.

DIRECTIONS FOR USE:

Surface Preparation - the concrete must be clean and rough. All oils, dirt, debris, paint and unsound concrete must be removed.

Mix 1-1.5 parts of powder into 1 part of clean potable water. Small quantities can be mixed by hand. Care should be taken to ensure that **CEMTEC CRACK FILLER** is thoroughly mixed.

APPLICATION:

As a crack filler: Remove all loose particles or wallpaper from holes. The mixed product should be pressed firmly into the cracks by spatula, putty knife or trowel.

As a finish coat: The mixed product should be applied by trowel for leveling the uneven concrete surfaces. Smooth the surface with the sand paper after material is dried.

Curing : **CEMTEC CRACK FILLER** does not require curing with standard methods for most applications. Under hot windy or rapid drying conditions a fog spray or wet cure for 24 hours is recommended after final set of material.

CLEAN-UP:

Clean tools and equipment with water before the material hardens.

PACKAGING:

CEMTEC CRACK FILLER is available in 20 kg bags.

QUALITY STATEMENT

CMCI manufacture its products at their manufacturing facility in Saudi Arabia as per the Quality Procedures certified to conform with Quality Management System described in ISO 9000 series

CMCI provides a comprehensive technical support system for its full range of high performance construction products. CMCI also offers full technical field support to consultants, Architects, Contractors, applicators and End Users

The Technical Specification information and recommendation given are based on the current technical knowledge and the user or his representative is recommended to check the suitability of the product. CMCI reserves the right to amend the technical characteristic of the product as part of ongoing research and development. As the work execution is beyond the direct and continuous control of CMCI no guaranty and or responsibility is assumed on the performance of work completion executed with use of our products.