

CEMTEC DAMP PROOFING BITUMINOUS COATING

SOLVENT BASED

DESCRIPTION

CEMTEC DAMP PROOFING BITUMINOUS COATING is a cold applied anti-corrosive Bitumen coating comprising selected Grade Asphalt and fast drying solvent to act as a damp proofing membrane. It can also be used as a protective coating below ground.

USES

Protective anti-corrosive, waterproofing coating for metal and concrete surfaces, such as escape stairs, ladders, storage tanks, gutters, down pipes, fences, etc.

ADVANTAGES

- Excellent adhesion and self-healing properties
- Easy application and smooth finish
- Anti-corrosive coating
- It has good resistance to mild acids, alkalis and salts.
- Exhibits soil bacteria resistance.

PREPARATION

- Application surface should be cleaned and free from dust, grease or rust, etc. Surface for application may be slightly damp but not wet.

APPLICATION

- **CEMTEC DAMP PROOFING BITUMINOUS COATING** can be applied with Brush, Roller or Spray.
- Minimum of two coats should be applied.

PRECAUTION

- **CEMTEC DAMP PROOFING BITUMINOUS COATING** has fast evaporating solvent, hence, containers should always be closed.
- Successive coats will be applied after previous coat is dry.
- Read health and safety instructions before use.

COVERAGE

2m²/litre at 300 microns DFT

STORAGE

Long life in air tight closed containers under temperature 5 - 30° C.

CLEANING

CEMTEC DAMP PROOFING BITUMINOUS COATING can be cleaned with any suitable petroleum solvent.

PACKING

Available Standard 20 Ltr. Pail and 200 Ltrs. Drum

TECHNICAL DATA

Application Standard BS . 3416 TYPE I

PROPERTIES

Color
Specific Gravity
Solid content
Drying Time
(Surface tack free)
Over Coating Interval
Corrosion Test
with 3% NaCl
Flash Point

SPECIFICATIONS

Shiny black Liquid
0.90 - 1.0
60% by weight (approx.)
4 hours
24 hours
Stable & No Blistering
Min 32° C.

HEALTH AND SAFETY INSTRUCTIONS

- **CEMTEC DAMP PROOFING BITUMINOUS COATING** is solvent based and gives out inflammable vapors before drying which may have narcotic effect if inhaled or absorbed through skin.
- Use protective clothing, gloves, masks, goggles, etc.
- Avoid contact with skin, eyes or inhalation. In such events remove the person to fresh air, irrigate with clean water over affected area at first instance and call for medical attention.

QUALITY STATEMENT

CMCI manufacture its products at their manufacturing facility in Saudi Arabia as per the Quality Procedures certified to conform with Quality Management System described in ISO 9000 series

CMCI provides a comprehensive technical support system for its full range of high performance construction products. CMCI also offers full technical field support to consultants, Architects, Contractors, applicators and End Users

The Technical Specification information and recommendation given are based on the current technical knowledge and the user or his representative is recommended to check the suitability of the product. CMCI reserves the right to amend the technical characteristic of the product as part of ongoing research and development. As the work execution is beyond the direct and continuous control of CMCI no guaranty and or responsibility is assumed on the performance of work completion executed with use of our products.